

24'' Back Bar Cooler/Direct Draw Beer Dispenser: Solid door

- Balanced refrigeration system designed to operate at 33°F~41°F.
- Stainless steel floor and inner walls, standard.
- Self-closing doors with locks.
- Stainless steel option.
- Space-saving side mounted evaporator optimizes interior cabinet space.
- ETL & NSF-7 approved for packaged and bottle product.
- Tempered glass to avoid injury by broken glass.
- LED light .
- Easily accessible condenser coil for cleaning, and easy service access.



UDD-24-48



UDD-24-60



UDD-24-72

Model	UDD-24-48	UDD-24-60	UDD-24-72
Doors	2	2	3
Temperature range	33°F~41°F (0°C~5°C)	33°F~41°F (0°C~5°C)	33°F~41°F (0°C~5°C)
Capacity	11.8 cu.ft. / 335 L 2*1/2 Barrels	15.8 cu.ft. / 446 L 2*1/2 Barrels	19.6 (cu.ft.) / 556 L 3*1/2 Barrels
Shelves	4	4	6
Exterior dimensions (LxDxH)	48 7/8 × 24 3/8 × 36 1/4 (in) 1240×620×920 (mm)	60 3/4 × 24 3/8 × 36 1/4 (in) 1544×620×920 (mm)	72 3/4 × 24 3/8 × 36 1/4 (in) 1848×620×920 (mm)
Interior dimensions (LxDxH)	36 1/4 × 18 1/2 × 30 1/2 (in) 920 × 470 × 775 (mm)	48 1/4 × 18 1/2 × 30 1/2 (in) 1224 × 470 × 775 (mm)	60 1/8 × 18 1/2 × 30 1/2 (in) 1528 × 470 × 775 (mm)
Compressor HP	1/3+	1/3+	1/3+
Voltage	115V/60Hz 230-240V/50Hz	115V/60Hz 230-240V/50Hz	115V/60Hz 230-240V/50Hz
Amps	6.4	6.4	7.4
NEMA Config	5-15P	5-15P	5-15P
Loading quantity	54 pcs / 40'GP	48 pcs / 40'GP	36 pcs / 40'GP



UDD-24-48SS



UDD-24-60SS



UDD-24-72SS

Model	UDD-24-48SS	UDD-24-60SS	UDD-24-72SS
Doors	2	2	3
Temperature range	33°F~41°F (0°C~5°C)	33°F~41°F (0°C~5°C)	33°F~41°F (0°C~5°C)
Capacity	11.8 cu.ft. / 335 L 2*1/2 Barrels	15.8 cu.ft. / 446 L 2*1/2 Barrels	19.6 (cu.ft.) / 556 L 3*1/2 Barrels
Shelves	4	4	6
Exterior dimensions (LxDxH)	48 7/8 × 24 3/8 × 36 1/4 (in) 1240×620×920 (mm)	60 3/4 × 24 3/8 × 36 1/4 (in) 1544×620×920 (mm)	72 3/4 × 24 3/8 × 36 1/4 (in) 1848×620×920 (mm)
Interior dimensions (LxDxH)	36 1/4 × 18 1/2 × 30 1/2 (in) 920 × 470 × 775 (mm)	48 1/4 × 18 1/2 × 30 1/2 (in) 1224 × 470 × 775 (mm)	60 1/8 × 18 1/2 × 30 1/2 (in) 1528 × 470 × 775 (mm)
Compressor HP	1/3+	1/3+	1/3+
Voltage	115V/60Hz 230-240V/50Hz	115V/60Hz 230-240V/50Hz	115V/60Hz 230-240V/50Hz
Amps	6.4	6.4	7.4
NEMA Config	5-15P	5-15P	5-15P
Loading quantity	54 pcs / 40'GP	48 pcs / 40'GP	36 pcs / 40'GP

EQUIPCHEFS INC, 12922 Hempstead Hwy Houston Texas 77040
Tel: 713 690 1231 Fax: 713 690 1091 E-mail: texasre@yahoo.com
Website: www.equipchefs.com